

All technical data presented represent typical results, unless stated otherwise as min/max values. No guarantee is made that material will meet exactly the values shown.

Coin Cell Parts

Our coin kits and crimpers are meant to be used together. If you're using another vendor's coins or crimper, ask us how we can accommodate your lab set-up.

Coin Cell Nomenclature: CR2016, for example, indicates 20mm diameter x 1.6mm height.

CR2016 (Case, cap, & gasket)

Case: SUS316L Cap: SUS316L Gasket: PP
1,000 kits minimum order quantity

Also available with Al-cladding in bottom of case; 1000 kits minimum order

CR2025 (Case, cap, & gasket)

Case: SUS304 Ni-plated on the outside layer Cap: SUS304 Ni-plated on the outside layer Gasket: PP
500 kits minimum order quantity

CR2032 (Case, cap, & gasket)

Plain case: SUS316L Cap: SUS316L Gasket: PP
500 kits minimum order quantity

or Al-CVD case for CR2032 (Al-CVD Case, SUS316L Cap & PP Gasket)

AL-CVD Case on SUS316L. Cap: SUS 316L Gasket: PP
100 kits minimum order quantity

CR2325 (case, cap, & gasket) -- NO LONGER AVAILABLE FROM HOHSEN

Case & Cap: SUS304 Gasket (attached to the cap): Elastomer No. 9103-54
1,000 kits minimum order quantity

Wave Springs: SUS 316L

15 mm dia. x 1.4 mm H

500 pieces minimum order quantity

Spacer Disks: SUS 316L

15.5mm dia. x 0.5mm T or 15.5mm dia. x 1.0mm T

16.0mm dia. x 0.5mm T or 16.0mm dia. x 1.0mm T

500 pieces minimum order quantity for above types

Aluminum spacers are available

Custom thicknesses and diameters are available upon request

18650 cans and 9 parts

Also available are mesh kits for metal-air batteries as well as other forms and sizes.

Application: Advanced energy

Product type: Consumables, Components

Production scale: Lab, Pilot, Commercial

Search tags: Hohsen, Components, Coin, Coins, Kits (18650 kits)